



# SorbAll®

## ACOUSTIC CEILING CLOUDS

SorbAll Acoustic Ceiling Clouds are perfect for the reduction of sound in ceiling areas. They are suspended horizontally with D-Rings (for panels up to 4' x 4') or T-grid attachment for larger panels.

The SorbAll Acoustic Ceiling Clouds are constructed with a 6-7# PCF rigid fiberglass absorber core. The edges are available in natural or chemically hardened and are available in 4 edge profiles.

### FINISHES

Guilford of Maine FR701 Style 2100 is the industry standard. Hundreds of approved decorative fabrics are also available from numerous manufacturers including, but not limited to: Guilford of Maine, Maharam, Design Tex and Knoll. Customers may also specify their own fabric, provided the material meets manufacturing requirements.

### ACOUSTICAL

NRC Rating

1/2" Thick	_____	.50 – .60
1" Thick	_____	.80 – .90
2" Thick	_____	1.05 – 1.25


### SIZING

All panels are custom made with sizing up to a maximum 4' x 10' and with thickness ranging from 1/2" – 4' thick.

### MOUNTING OPTIONS

D-Rings, T-Grids or Rotofast Cloud Anchors

### EDGE DETAILS



Square

Miter

Bevel

Radius

- Excellent acoustical performance
- High-quality, economical, multi-purpose panels
- Class A fire rated
- Standard, designer or C.O.M. fabrics
- Various mounting options
- Custom sizes and shapes

#### Noise Control Specialist

10723 Plano Road, Suite 100  
Dallas, Texas | 75238

Office: 214.382.2951 | Fax: 214.382.2952

[www.noisecontrolspecialist.com](http://www.noisecontrolspecialist.com)